



Data Sheet HTPS5200-4PGE2GF

Product Appearance:



Key Features:

Ports: Provide 4*10/100/100Mbps PoE ports and 2* Gigabit SFP Uplink

PoE Standard: IEEE802.3af/at Power over Ethernet (PoE) Compliant

Total Power: Total power budget of 65W and 30W for all single PoE ports

Self-adaption: RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

Extend Mode: Extend PoE up to 250m on one single cable

Wide Application: Designed for Wifi AP and IP Security camera.VoIP etc

6KV Surge protection: Protect the device from lighting surges and others electrical hazards

Considerate Design: Exquisite compact size with fanless design

Easy to use: Plug and play, No configuration required

Model	HTPS5200-4PGE2GF
Fixed port	2* Gigabit SFP Port 4* 10/100/1000 POE ports
POE	65W
Exchange capacity	12G; 8K MAC
Packet forwarding rate	8.93Mpps
Operating temperature	-20~55°C
storage temperature	-40~70°C
Working humidity	5% to 95% non-condensing
Storage humidity	5% to 95% non-condensing
physical dimension	202mm*104mm*44.5mm
Total Weight	0.72kg
Input voltage	AC100-240V 50/60Hz
ESD Protection	6KV
Certificate	CE mark, Commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS

Solution Diagram:

