



## **Data Sheet HTPS5200-8PGE2GE**

## Product Appearance:



## Key Features:

**Ports:** Provide 8\*10/100/100Mbps PoE ports and 2\* Gigabit Uplink

**PoE Standard:** IEEE802.3af/at Power over Ethernet (PoE) Compliant

**Total Power:** Total power budget of 120W and 30W for all single PoE ports

**Self-adaption:** RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

**Extend Mode:** Extend PoE up to 250m on one single cable

**Wide Application:** Designed for Wi-Fi AP and IP Security camera. VoIP etc

**6KV Surge protection:** Protect the device from lighting surges and others electrical hazards

**Considerate Design:** Exquisite compact size with fanless design

**Easy to use:** Plug and play, No configuration required

<b>Model</b>	<b>HTPS5200-8PGE2GE</b>
Fixed port	2* Gigabit Uplink Ports 8* 10/100/1000 POE ports
POE	120W
Exchange capacity	20G; 8K MAC
Packet forwarding rate	14.88Mpps
Operating temperature	-20~55°C
storage temperature	-40~70°C
Working humidity	5% to 95% non-condensing
Storage humidity	5% to 95% non-condensing
physical dimension	270mm*180mm*44.5mm
Total Weight	1.4kg
Input voltage	AC100-240V 50/60Hz
ESD Protection	6KV
Certificate	CE mark, Commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS

# Solution Diagram:

