



## **Data Sheet HTPS5220-24PGE4GC**

## Product Appearance:



## Key Features:

**Ports:** Provide 24\*10/100/100Mbps PoE ports and 4\* Gigabit Combo Uplink

**PoE Standard:** IEEE802.3af/at Power over Ethernet (PoE) Compliant

**Total Power:** Total power budget of 400W and 30W for all single PoE ports

**Self-adaption:** RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

**Extend Mode:** Extend PoE up to 250m on one single cable

**Wide Application:** Designed for Wi-Fi AP and IP Security camera. VoIP etc

**6KV Surge protection:** Protect the device from lightning surges and others electrical hazards

**Considerate Design:** Exquisite compact size with fanless design

**Easy to use:** Plug and play, No configuration required

<b>Model</b>	<b>HTPS5220-24PGE4GC</b>
Fixed port	4* Gigabit Combo Uplinks 24* 10/100/1000 POE ports
POE	400W
Exchange capacity	64G; 16K MAC
Packet forwarding rate	47.62Mpps
Operating temperature	-20~55°C
storage temperature	-40~70°C
Working humidity	5% to 95% non-condensing
Storage humidity	5% to 95% non-condensing
physical dimension	440mm*290mm*44.5mm
Total Weight	4.5kg
Input voltage	AC100-240V 50/60Hz
ESD Protection	6KV
Certificate	CE mark, Commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS

# Solution Diagram:

